



## Ozone Generator

The professional choice for  
odor neutralizing



- Eliminates smoke, pet odor, mold, mildew and more
- Effective for areas up to 60,000 cubic ft
- Tested and proven to maintain proper activated oxygen levels
- Quickly deodorizes hotel/motel, hospital and meeting rooms
- No plates or UV tubes to maintain



## Destroy the source of odor

Tornado Ozone Generator odor neutralizer attacks odor-causing bacteria and molecules and leaves pure fresh oxygen in its place. The large-capacity unit is ideal for commercial use. It is excellent for smoke damage, mold, mildew, pet odor and other sources of odor commonly found in building maintenance and refurbishing.

The Ozone Generator will minimize odor in any indoor location, including basements, kitchens, bathrooms and more. It also provides rapid deodorizing for hotel/motel rooms, meeting rooms, used cars and boats. The unit requires no routine maintenance and is effective for areas up to 60,000 cubic feet..

## How it works

Ozone occurs naturally in the environment. The most common exposure to ozone occurs when there is a thunder storm; the fresh smell you notice is from the ozone released during the storm. Tornado's Ozone Generator creates ozone by exposing oxygen in the atmosphere to high-density ceramic and stainless steel electrodes. When the oxygen in the air comes in contact with the electrodes, it brings the oxygen molecules (O2) together to form ozone (O3). The O-Z unit injects the ozone into the air. When the ozone is introduced, it disperses and mixes with the air.



**12-HOUR TIMER**  
12-hour timer with power supply overload protection



**POWERFUL FAN / POWER SUPPLY**  
Has a 100 CFM fan with ball bearings for extended service life



**EASY STORAGE/TRANSPORTING**  
Durable poly housings stack for easy storage or transporting.

PRODUCT	OZONE GENERATOR
Catalog Number (Kit)	77011
Machine Dimensions (LxWxH)	12 in x 11 in x 12 in 30 cm x 28 cm x 30 cm
Weight	7.3 lbs. / 3.3 kg
Air Movement	1.5 grams per hour / 7 p.p.m
Timer	12-Hour
CFM	100
Max Effectiveness	60,000 cubic ft. / 1,699 cubic m
Electrodes	Gas filled arc module
Power Cord	5 ft. grounded / 2 m grounded
Parts / Labor Warranty	1 year*

\* Note: See full warranty for details